

Heavy Duty Vibration Meter



Measures Acceleration, Velocity and Displacement plus a PC interface

Stores the maximum and minimum values for later recall

Features:

- Ranges — Acceleration (peak): 656ft/s² (200m/s²), Velocity (peak): 7.87in/s (200mm/s), Displacement (peaktopeak): 0.078in (2mm)
- Remote vibration sensor with magnetic adapter on 39"(1m) cable
- Wide frequency range of 10Hz to 1kHz
- Resolution to 2ft/s² (0.5m/s²), 0.02in/s (0.5mm/s), and 0.001in (0.005)mm
- Basic accuracy of $\pm(5\% + 2 \text{ digits})$
- RMS or Peak Value measurement modes
- Manual/Auto store/recall up to 500 readings
- Optional Windows[®] 95/98/NT/2000/XP compatible software allows captured readings to be downloaded to your PC for further analysis
- Data Hold freezes the reading in the display
- Auto shutoff saves battery life
- 9V battery power or optional AC adaptor
- Dimensions: 7.1 x 2.8 x 1.3" (180 x 72 x 32mm); Weight with Probe: 0.87lbs (395g)
- Complete with remote sensor, magnetic mount, 9V battery, protective rubber holster with stand, and hard carrying case

Applications:

- Motors, bearings
- Fans
- Pumps
- Rotating machinery
- Plant maintenance

Ordering Information:

407860.....Heavy Duty Vibration Meter, Mounted pickup
407860NIST407860 with Calibration Traceable to NIST
156119.....117V AC Adaptor
156221.....220V AC Adaptor
407001.....Data Acquisition software and cable
407001USB.....USB adaptor for 407001



สนใจติดต่อ บริษัท เอเม็ท จำกัด โกสุมร่วมใจ 31 ซอย 37 แยก 2 คอนเมือง กทม 10210

โทร.02-5038900, 02-5038929, แฟกซ์ : 02-9810181, Email : sales@amet.net , Web: www.amet.net