

เครื่องวัดความชื้นไม้ และวัสดุ แบบสัมผัส รุ่น 200XL

Hand-Held Moisture Meter Delta 200-XL

เครื่องวัดความชื้นของไม้และวัสดุแบบสัมผัส ใช้งานง่าย เหมาะกับไม้ที่แปรรูปแล้วและยังไม้แปรรูป

- วัดได้ลึก 100 มม
- ช่วงการวัดได้ 3% - 80 %
- ตอบสนองเร็ว
- วัดไม้ได้กว่า 400 ชนิด

Around the measuring springs a constant high-frequency field is build-up, which allows thousands of measurements, taken per sec., on the material to be measured. Thus a very accurate measuring result is assured. The measured value will be indicated in a few seconds after the measuring springs have contact with the material to be measured.

Which timber can be measured?

All together 18 (eightteen) selectable woodgroups means a much better adjustment to the different types of wood according to the density / cubic meter (beginning from 100 kg up to 950 kg).

More then 240 local types of timber as well as exotic types of timber are divided into the wood-groups.

Beginning with a great number of softwood, such as spruce, fir, poplar etc. (woodgroup H2) up to european and exotic hardwood, such as quebracho, ebony and azobe (woodgroup H10).

The tolerance (correct application) is +/- 1%.

The measuring range: 3% - 80% wood moisture.

The max. measuring depth for measurements taken on timber is 100 mm.

The unit is equipped with a special HOLD function.

This HOLD function allows to store the measured value on the display.

Why does one need the HOLD function?

Very often it happens that the measured and displayed value can't be read directly. E.g. during measurements taken inside of a wooden pile, inside the drying kiln or at the bottom of a wooden board / beam.

This special function is then very useful.

A build in BUZZER indicates a specified limit-value

If the measured value goes higher than a specified limit-value, the buzzer will beep.

This function is very helpful for fast timber selection.



เครื่องวัดความชื้นไม้ และวัสดุ และ สัมผัส รุ่น 200XL

Hand-Held Moisture Meter Delta 200-XL

Additional advantages of the Delta 200-XL

- Very convenient
- Small and handy; it finds its place even in a vest pocket
- The material to be measured will NOT be damaged during measurements
- No drive-in electrodes
- Automatic zero-correction
- Woodgroups selectable
- Maximum measuring depth is 100 mm

Indispensable for:

- Glaziers
- Architects
- Workmen in buliding trade
- Furniture shops
- Floor tilers
- Joiners
- Carpenters
- Perquetry

Dimensions:

Approx. 132 x 62 x 30 mm (H x W x D)

Weight:

Approx. 150 g with battery

สนใจติดต่อ บริษัท เอเมท จำกัด โทร.02-9079421-2 , 02-9077480-3 แฟกซ์ 02-9078643 , 02-9079878