

Used for high intensity measurements up to 400,000 Lux and 40,000 Foot candles



#### FEATURES

- Compact and rugged design features large display and bargraph
- Wide measuring ranges:
  - EH301 - 40,000 Fc in 4 ranges and 400,000 Lux in 5 ranges
  - EH311 - 20,000 Fc in 4 ranges and 20,000 Lux in 4 ranges
- MIN/MAX readings
- Relative function for zero or difference from reference value
- Cosine and color corrected measurements
- Auto power off; low battery and overrange indication
- Utilizes precision silicon photodiode sensor with 5ft coiled cable for easy storage
- Complete with built-in stand, remote sensor with protective cover, protective holster, and 6 AAA batteries

#### ADDITIONAL FEATURES FOR MODEL EH301

- Large display with bargraph
- Peak hold captures short light pulses to 100 $\mu$  Sec
- Relative function for zero or difference from reference value



SPECIFICATIONS

Range	Resolution	Basic Accuracy
Light Intensity EH301 Lux: 40, 400, 4000, 40000, 400000Lux Fc: 40, 400, 4000, 40000Fc	0.01	± 3% rdg + 5 digits
EH311 Lux: 20, 200, 2000, 20000 Lux Fc: 20, 200, 2000, 20000Fc	0.01	± 3% rdg + 5 digits
Dimensions	5.9 x 2.8 x 1.4" (150 x 72 x 33mm)	
Weight	8.3 oz (235g)	

CAT NO.	MODEL	DESCRIPTION
EH301	EA30	EasyView Light Meter
EH311	EA31	EASYVIEW LIGHT METER