

### Applications

- Designed for simple one hand operation.
- Size 6.7"x1.7"x1.6"(170 x 44 x 40 mm)
- Weight 220 gms.
- Display: LCD
- Range : From 20 to 200,000 lux
- Functions: Maximum/minimum
- Backlit display.
- Resolution : 0.01 lux
- Cosine Response :  $f^2 < 2\%$
- CIE ( $\lambda$ ):  $f^1 < 2\%$ ,  $< 3\%$ ,  $< 5\%$ ,  $< 8\%$ ,  $v(\lambda)$  Match
- Spectral Response : CIE photopic
- Response time : 3 per second.
- Acceptance Angle :  $f^2 < 2\%$  cosine corrected (150°)
- Highly accurate  $f^1$  Compensation and Diffuser  $f^2 < 2\%$
- Valox Housing to Withstand Accidental Drops
- Photometric Formulas : 10,764 : footcandles = 1 Lux (lumens/meter<sup>2</sup>)
- Range : 0-20 lux, 0- 200 lux ,0- 2,000 lux ,0- 20,000 lux ,0- 200,000 lux
- Accuracy : for CIE standard illuminateA(2856K): ( $\pm$  %rdg+10dgts)
- Battery: AAA 4 pieces 1.5V
- Accessories: Carrying case, manual in English.
- Warranty: 1 Years.!!



ENG-LVD  
DLM 530