

เครื่องวัดความสั่นสะเทือนแบบพกพา รุ่น EN-202-KIT

ENTRON Heavy Duty Vibration Meter. Model EN-202-KIT



EN-202 Overall vibration meter and electronic stethoscope for plant maintenance and for performing pdm maintenance programs. This meter is simple to operate with only two switches on either side of the meter. The unit is suitable for measuring vibration levels in roller bearings and moving machinery. Unit features a digital LCD display and also features an industrial type headphone that can be used for listening to the sound of roller bearings. This is a cost effective method of enhancing machine reliability in your plant. The unit features an ISO 2372 chart built into the front panel, enabling you to do direct comparison of your measured vibration results with that of industry standards, thus eliminating guesswork and simplifying routine maintenance tasks.



Features

- Measures vibration in:
 - Acceleration – suitable for 10,000 + rpm and high speed machinery applications.
 - Velocity – per ISO 2372. Suitable for general purpose vibration measurements and is ideal for Monitoring machinery, and for performing trending. (pdm maintenance)
 - Displacement. – perfect for low speed heavy machinery.
- Electronic Stethoscope – used with Included headphones for listening to the sound of the roller bearings and to determine lubrication requirements.
- Measures vibration in both RMS and in PEAK values.
- Auto power off for conserving battery life.
- Data Hold for recording current reading on display.

Specifications per Model:

- Amplitude Ranges:

Units	Ranges
Acceleration	0 ~ 19.99 G's (peak & RMS.)
Velocity	0 ~199.9 mm/s (peak & RMS.)
Displacement	0 ~199.9 μ m. (pk-pk)



General Specifications (All Models)

- Accuracy All Ranges: \pm 1% + 3 LSD.
- Frequency Ranges:
 - 5 ~ 10,000 Hz.
- Display Indications:

สนใจติดต่อ บริษัท เอเม็ท จำกัด 11/13 หมู่ 5 ถ.สุคนธ์สวัสดิ์ แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230

โทร.02-9077480-3 ,02-9079421-2,แฟกซ์ : 02-9079878 , Email : sales@amet.net , Web: www.amet.net



ENTRON Heavy Duty Vibration Meter. Model EN-202-KIT

- LCD 3.5 digit. With LED Low Battery Indication warning.
- Vibration Sensor:
 - Piezoelectric Accelerometer 100mV/G.
- Output:
 - Audio: (3.5 mm) mini plug.
 - Sensor power: 28 V. DC @ 2 mA.
- Power Supply:
 - 7.2V. DC supplied by 2 cell Lithium Ion rechargeable batteries with Automatic protection circuit.
 - Battery Usage time:
18 Hours continuous before needs recharging. (Typical charge once per 14 or 28 days per usage)
 - Battery Lifetime: 500 charge cycles (Approximately 1.5 years to 2 years of normal use)
- Environmental:
 - Meter: -10 to 50°C., Accelerometer -10 to 70°C
- Physical:
 - Dimensions: 152 x 83 x 32 mm.
 - Weight: 1.2 kg.
- Standard Accessories All Included:
 - Instruction manuals in English and Thai language.
 - Soft carrying case., and Stainless Steel Stinger probe.
 - Piezoelectric Accelerometer Model AC-102-1A.
 - Automatic Recharger with red and green charging LED.
 - Industrial type Noise Reducing Headphones
 - Rare Earth Al-Ni-co magnet for accelerometer.
- Price and ordering information.
 - EN-202 Vibration Meter. Includes Vibration meter, and all Standard Accessories. (Please Specify 110V.AC or 220V. ac charger).
 - Price: USD\$1,050.
- Warranty Information: The vibration meter is unconditionally warranted for Normal use for period of 5 years from date of purchase. Warranty for accelerometer, headphones and accessories is 1 year.



Audio Output for Headphones



BNC Input for Accelerometer



Battery Charging Jack.