



DSL-332 Features:

4 Digit LCD display.

Max hold function.

Fast & slow dynamic characteristic models.

Level Range from 35 ~ 130dB.

Resolution 0.1dB, Accuracy ± 1.5 dB.

A & C Frequency Weightings.

AC/DC Signal output.

Low Battery Indication.

Reset Function.

Self-Calibration 94dB.

- DSL-332 SPECIFICATIONS:

- Specifications : Standard applied : IEC 651 Type2
- Level Range:
- A LO (Low) - Weighting: 35- 90dB
- A HI (High) - Weighting: 75-130dB
- C LO (Low) - Weighting: 35- 90dB
- C HI (High) - Weighting: 75-130dB
- Resolution: 0.1dB
- Frequency Range: 31.5Hz to 8KHz
- Accuracy: +/- 1.5dB (ref 94dB @1KHz)
- Dynamic Range: 55dB
- Frequency Weighting: A, C
- Time Weighting: Slow & Fast
- Maximum Hold: Decay < 1dB/3min

สนใจติดต่อ บริษัท เอเม็ท จำกัด 11/13 หมู่ 5 ถ.สุขนครสวัสดิ์ แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230



- Microphone: Electret condenser microphone
- Calibration: Electrical calibration by using the internal oscillator
- (1KHz sine Wave at 94dB)
- Auxiliary Outputs: AC conditioned, 0.55Vrms corresponding to
- each range step, impedance: 600W
- DC conditioned, 10mV/dB (nominally)
- impedance: 100W
- Operating Condition: 0oC to 40oC < 80% R. H.
- Storage Condition: -10oC to 60oC < 70% R.H.
- Display: 4 digitals
- Power Supply: one 9V battery
- Dimensions: 240mm(L)x68mm(W)x25mm(H)
- Weight: 215g
- Accessories: Instruction Manual, 9V Battery, Carrying Case, Screwdriver, Windscreen.
- Tripod Stand (optional DSL-330-ST)