



Digital Storage Oscilloscope (Color DSO GDS-806C/ GDS-810C/ GDS-820C / GDS-840C ; Mono : GDS-806S/ GDS-810S/ GDS-820S/ GDS-840S)

GDS-840C :250 MHz Display System:5.7 LCD, Color DSO
GDS-840S: 250 MHz Display System:5.7 LCD, Mono DSO
GDS-820C :150 MHz Display System:5.7 LCD, Color DSO
GDS-820S :150 MHz Display System:5.7 LCD, Mono DSO
GDS-810C :100 MHz Display System:5.7 LCD, Color DSO
GDS-810S :100 MHz Display System:5.7 LCD, Mono DSO
GDS-806C Bandwidth:60MHz, Display System:5.7 LCD, Color DSO
GDS-806S Bandwidth:60MHz Display System:5.7 LCD, Mono DSO



Color Digital Storage Oscilloscope

Specifications:

- GDS-840C/ 840S Features:
 - 250MHz Bandwidth
 - 125k Long Memory and 12 Division Horizontal Display
 - 25GS/s Sampling Rate for Repetitive Waveforms
 - Advanced Trigger:Pulse Width,TV Line,Event Delay And Time Delay
 - Go-NoGo and Auto Setup Sequence
 - FFT Function
 - Built-In Help Manual, Multi-Language and PC Software
 - Standard Interface: USB, RS-232C, Printer Port, Go/NoGo Output
 - Option: GPIB Interface
- GDS-820C/ 820S Features:
 - 150MHz Bandwidth
 - 125k Long Memory and 12 Division Horizontal Display
 - 25GS/s Sampling Rate for Repetitive Waveforms
 - Advanced Trigger:Pulse Width,TV Line,Event Delay

สนใจติดต่อ บริษัท เอเม็ท จำกัด 11/13 หมู่ 5 ถ.สุขนครสวัสดิ์ แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230

โทร.02-9079421-2 , 02-9077480-3, แฟกซ์ : 02-9079878 , Email : sales@amet.net , Web: www.amet.net



- And Time Delay
 - Go-NoGo and Auto Setup Sequence
 - FFT Function
 - Built-In Help Manual, Multi-Language and PC Software
 - Standard Interface: USB, RS-232C, Printer Port, Go/NoGo Output
 - Option: GPIB Interface
- GDS-810C/ 810S
 - 100MHz Bandwidth
 - 125k Long Memory and 12 Division Horizontal Display
 - 25GS/s Sampling Rate for Repetitive Waveforms
 - Advanced Trigger : Pulse Width , TV Line, Event Delay and Time Delay
 - Go/NoGo and Auto Setup Sequence
 - FFT Function
 - Built-In Help Manual, Multi-Language and PC Software
 - Standard Interface: RS-232C
 - Option: GPIB, USB Interface, Printer Port, Go/NoGo Output
 -
 -
- GDS-806C/ 806S
 - 60MHz Bandwidth
 - 125k Long Memory and 12 Division Horizontal Display
 - 25GS/s Sampling Rate for Repetitive Waveforms
 - Advanced Trigger : Pulse Width , TV Line, Event Delay and Time Delay



- Go/NoGo and Auto Setup Sequence
- FFT Function
- Built-In Help Manual, Multi-Language and PC Software
- Standard Interface: RS-232C
- Option: GPIB, USB Interface, Printer Port, Go/NoGo Output