



### Minimaster HT and HTC

The Minimaster HT offers a

- wide measuring range (wet and dry)

- corrections for 20 wood groups -corrections for different wood temp. (HT for °F and HTC for °C).

Ideal for measuring cold lumber outside or hot lumber in a kiln. Easy-to-read display with resolution of 0.1% for entire range. An electrode or probe is required.

Ideal to obtain >in-kiln readings using

Lignomat's PK Probe and Cable. These meters can also >measure the moisture in building materials such as concrete, drywall or plaster (Electrode E16).

#### **Designed for Sturdiness and Ease of Operation:**

Push buttons are positioned for one hand operation, while the other hand handles the electrode. All moisture readings are instantly displayed and corrected for the pre-set wood species and wood temperature.

Like the Mini-Lignos, these sophisticated meters have proven to perform well in the rough mill environment with day-to-day usage.

#### **Specifications for Minimaster HT/HTC**

- - - Range: 5-75% dependent upon species
- - - Species Corrections: 20 Settings
- - - Wood Temperature Correction for °F: Minimaster HT: 0° - 210°F
- - - Wood Temperature Correction for °C: Minimaster HTC: -15° - 95°C
- - - BNC Connector to connect cable to electrode, remote probes or EMC Sensor
- - - One 9-Volt Battery for over 30,000 readings
- - - Size: 2"L x 5"W x 1/2"H (50 x 125 x 12.5mm)
- - - Weight: 5 ozs (125g)
- - - Case: depends upon choice of Electrodes,.