



FEATURES

- UV irradiance measurement for UVA and UVB
- UV detector spectrum from 290 to 390nm
- High and low measurement range
- Separate UV light probe permits measurements from any position
- LCD display
- Low battery indicator
- Ideal for a variety of industrial and laboratory applications including sterilization, virology, DNA research and much more

Please inquire for NIST certification

SPECIFICATIONS

Ranges	1999 uW/cm; 19990 uW/cm
Resolution	1 uW/cm (1999 uW/cm), 10 uW/cm (19990 uW/cm)
Spectrum	290 to 390 nm
Sampling Time	approximately 0.4 sec
Accuracy	± (4% full scale + 2 digits)
Unit Size	5.2" x 2.75" x 1"
Power Source	1 9-volt battery
Weight	7.7 oz

CAT NO.	MODEL	DESCRIPTION
---------	-------	-------------

สนใจติดต่อ บริษัท เอเม็ท จำกัด 11/13 หมู่ 5 ถ.สุขนครสวัสดิ์ แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230

โทร.02-9079421-2 , 02-9077480-3, แฟกซ์ : 02-9079878 , Email : sales@amet.net , Web: www.amet.net



IT3401 UV340 Ultra Violet Light Meter

Supplied with UV sensor probe and hard case