

Pen DMM with Non-Contact Voltage Detector



Autoranging MultiMeter with rotary dial
With a retractable tip for safe storage

Features:

- Large 2000 count high contrast LCD display
- Non-Contact Voltage detection with visible and audible alarm
- Autoranging with Data Hold, Range Hold, and Maximum Hold features
- Functions include AC/DC Voltage, Resistance, Continuity and Diode Test
- Auto Power off to conserve battery life
- Overload and low battery indication
- Meets IEC1010-1; CAT III-600V
- Complete with test lead with alligator clips, two 1.5V AAA batteries, and carrying case

Applications:

- AC live circuit detection
- Field Service troubleshooting tool for AC/DC circuits
- R & D and circuit board troubleshooting
- Digital circuitry testing



| Specifications | Range | Resolution | Basic Accuracy |
|---------------------|------------------------------|------------|----------------|
| Non-Contact Voltage | 50 to 600VAC | | |
| DC Voltage | 200mV, 2, 20, 200, 600V | 0.1mV | ±0.7% |
| AC Voltage | 200mV, 2, 20, 200, 600V | 0.1mV | ±0.8% |
| Resistance (Ω) | 200, 2k, 20k, 200k, 2M, 20MΩ | 0.1Ω | ±0.8% |
| Diode Test | 1mA @ 1.5V approx | | |
| Continuity Test | Audible beep <50 ohms | | |
| Dimensions | 8.2x1.5x1.1" (208x38x29mm) | | |
| Weight | 3.9oz (110g) | | |

Ordering Information:

381676Pen MultiMeter with Non-Contact Voltage Detector

สนใจติดต่อ บริษัท เอเมท จำกัด 31 ซอย โกสุมรวมใจ 37 แยก 2 แขวงดอนเมือง เขต ดอนเมือง กรุงเทพฯ. 10210

โทร.02-503-8900, แฟกซ์ : 02-981-0181, 02-981-0182 email : sales@amet.net , Web: www.amet.net

