

## Dial Stem Thermometers



### Choice of Flat Surface or Penetration Stem Thermometer

For use in liquids, semi-solids and solids

#### Features:

- **Flat Surface Stem (Model 392052):**  
High temperature range: -58 to 572°F (-50 to 300°C)
- **Penetration Stem (Model 392050):**  
Temperature range: -58 to 302°F (-50 to 150°C)
- Basic Accuracy of 2°F or 1°C
- 0.1° resolution to 199.9; 1° over 200°
- ON/OFF switch saves battery life
- Auto power off after 1hr of non use
- Dimensions: 5" (130mm) stainless steel probe with 2" (54mm) dial
- Weight: 1oz (29g); 1.3oz (30g) with protective sheath
- Includes 1.5V button battery, and plastic protective sheath with pocket clip for model 392050



Stem thermometer ideal for measuring temperature in HVAC applications such as air ducts, vents, and heaters.

Flat surface stem thermometer ideal for measuring high temperature on motors and other flat surface areas including grills.

#### Ordering Information:

- 392050 .....Dial Stem Thermometer  
392052 .....Dial Flat Surface Stem Thermometer

สนใจติดต่อ บริษัท เอเมท จำกัด 31 ซอย โกสุมรวมใจ 37 แยก 2 แขวงดอนเมือง เขต ดอนเมือง กรุงเทพฯ. 10210

โทร.02-503-8900, แฟกซ์ : 02-981-0181, 02-981-0182 email : [sales@amet.net](mailto:sales@amet.net) , Web: [www.amet.net](http://www.amet.net)

