

Oyster[®] Multifunction Process Calibrator

Precision Source and Measure

For thermocouples (Types J, K, and T), mA, mV, and V devices

Features:

- Source 0 to 24mA with 0.01mA resolution
- Measure 0 to 50mA (0.1mA resolution)
- Select Type J, K, or T thermocouple for precision calibrations in °F/°C or mV
- Output 0 to 1999mV or 0 to 10.00V
- Measure 0 to 19.99V
- Single/continuous step function for Voltage and Current
- Selfcontained 24V loop power supply drives current loads up to 1000Ω
- Memory for 5 user settable output values of each type for fast calibrations



Complete with six AA batteries, test leads with detachable alligator clips, temperature calibration cable with spade lug connector, carrying case, neckstrap, and 100V-240V AC Universal adaptor (50/60Hz)

Specifications	Range	Accuracy (of reading)
DC Source		
Current	0 to 24mA, 25% to +125%	±(0.075% + 1 digit) or ± 3 digits, whichever is greater
Voltage	0 to 10V	±(0.075% + 1 digit) or ± 3 digits, whichever is greater
Type J	58 to 1830°F (50 to 1000°C)	±(0.15% + 1.8°F or 1°C)
Type K	58 to 2498°F (50 to 1370°C)	±(0.15% + 1.8°F or 1°C)
Type T	184 to 752°F (120 to 400°C)	±(0.15% + 1.8°F or 1°C)
Loop Power	24V	±(10µV ± 1 digit)
Max. Load	1000 @ 24mA	
DC Measure		
Current	0 to 50mA, 25% to +230%	±(0.075% + 1 digit) or ± 3 digits, whichever is greater
Voltage	0 to 20V	±(0.075% + 1 digit) or ± 3 digits, whichever is greater
Type J	58 to 1830°F (50 to 1000°C)	±(0.15% + 1.8°F or 1°C)
Type K	58 to 2498°F (50 to 1370°C)	±(0.15% + 1.8°F or 1°C)
Type T	184 to 752°F (120 to 400°C)	±(0.15% + 1.8°F or 1°C)
Dimensions/Weight	3.8 x 4.7 x 2.0" (96 x 118 x 45mm)	12oz (340g)

Ordering Information:

412400Multifunction Calibrator
412400NIST412400 with NIST Certificate

สนใจติดต่อ บริษัท เอเมท จำกัด 31 ซอย โกสุมรวมใจ 37 แยก 2 แขวงดอนเมือง เขต ดอนเมือง กรุงเทพฯ. 10210

โทร.02-503-8900, แฟกซ์ : 02-981-0181, 02-981-0182 email : sales@amet.net , Web: www.amet.net

