



PRODUCT DATASHEET

Dual Laser InfraRed Thermometers



Indicates ideal measuring distance. Choose from 12" or 30" distance model where two laser points converge to 1" target spot

Features:

- Dual laser for accurate target
- White backlit dual LCD display
- Fast 0.15 second response time with Max display
- Adjustable emissivity increases measurement accuracy for different surface
- Adjustable High/Low set points with audible alarm alerts user when temperature exceeds the programmed set points
- Lock function for continuous readings
- Double molded housing
- Complete with pouch case and 9V battery





Specifications	42511	42512
Laser Convergence Distance	12" (30.5cm)	30" (76.2cm)
Range	-58 to 1100°F (-50 to 600°C)	-58 to 1832°F (-50 to 1000°C)
Repeatability	±0.5% or 1.8°F/1°C	±0.5% or 1.8°F/1°C
Basic Accuracy	±(1% of rdg + 2°F/1°C)	±(1% of rdg + 2°F/1°C)
Max resolution	0.1°F/°C	0.1°F/°C
Emissivity	0.10 to 1.00 Adjustable	0.10 to 1.00 Adjustable
Field of View (Distance to Target)	12:1	30:1
Dimensions	5.7x4x1.6" (146x104x43mm)	5.7x4x1.6" (146x104x43mm)
Weight	5.7oz (163g)	5.7oz (163g)

Ordering Information:

4251112" distance Dual Laser InfraRed Thermometer **42512**30" distance Dual Laser InfraRed Thermometer

42512-NIST....30" dist. Dual Laser InfraRed Thermometer w/ Calibration Traceable to NIST.

