

ExStik® 4-in-1 Water Quality Meter Kits

Surface measurements of Chlorine, pH, or ORP

Using a flat surface electrode

Features:

- 4-in-1 Water Quality Meter measures Chlorine, pH, ORP plus Temperature with interchangeable flat surface electrodes (included)
- Flat surface electrodes work in liquids, semi-solids and solids
- Memory stores and recalls 15 readings and saves last calibrated value
- Large 3-1/2 digit (2000 count) Digital display with bargraph (pH bargraph originates at neutral point 7.00pH)
- Automatic electronic self calibration for Chlorine and ORP; 1, 2 or 3 point buffer calibration for pH
- Data Hold, Auto shut-off and low battery indication
- Waterproof design floats in wet environment (IP57)
- Direct reading of Total Chlorine from low detection limit; Unaffected by sample color or turbidity
- Simultaneous display of ppm or pH and °C/°F Temperature
- Smart chip predicts pH electrode performance with "RENEW" indicator when replacement is needed
- "CAL" indicator alerts user to recalibrate pH electrode
- Automatic Temperature Compensation
- EX900 Kit Complete with ExStik® Chlorine meter, gel filled pH electrode, ORP electrode, protective sensor cap, 5 packs of 10 reagent tablets (50 tests), 4 plastic sample cups, weighted stand, pH 4, 7 & 10 buffer packs, four 3V SR44W batteries, carrying case, and neckstrap
- EX900-R Kit is same as EX900 but includes a refillable pH electrode
- EX800 Kit is same as EX900 but excludes ORP electrode



ExStik® Kit includes all the necessary accessories to measure Chlorine, pH, ORP, and Temperature.

Ordering Information:

- EX900ExStik® Kit 4-in-1 (pH – gel filled, ORP, Chlorine, Temperature)
- EX900-RExStik® Kit 4-in-1 (pH – refillable, ORP, Chlorine, Temperature)
- EX800ExStik® Kit 3-in-1 (pH, Chlorine, Temperature)
- PH103Tripak buffers (6ea. of 4, 7, 10pH & 2 Rinsing solutions)
- PH105Spare pH electrode
- PH115Spare Refillable pH ExStik® Electrode Module
- CL203Reagent tablets (10pk - 100 tests)
- CL204Reagent tablets (100pk - 1000 tests)
- CL205Spare Chlorine electrode
- RE305Spare ORP electrode
- EX007Spare sample solution cups with caps (24pk)
- EX010Extension Cable, 3ft (1 Meter) with probe weight for ExStik
- EX050Extension Cable, 16ft (5 Meter) with probe weight for ExStik

Specifications	EX613	EX622	EX623
pH	—	0.00 to 14.00pH	—
ppm	0.01 to 10.00ppm	—	—
mV	—	—	-999 to 999mV
Temperature	23° to 194°F (-5 to 90°C)	23° to 194°F (-5 to 90°C)	—
Resolution	0.01ppm	0.01pH	4mV
Accuracy	±10% of rdg. + 0.01ppm	±0.01pH	±1mV
Power	four LR44 button batteries		
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)		
Weight	3.85oz (110g)		

สน.ใจติดต่อ บริษัท เอเม็ท จำกัด 4/2, 4/60, 4/61 ถ.สุคนธสวัสดิ์ 30 แขวงลาดพร้าว เขตคลองพร้าว กรุง. 10230

โทร.02-9079421 , 02-9079878 , แฟกซ์: 02-9079878 , Email : sales@amet.net , Web: www.amet.net

