


## FM100 Formaldehyde (CH<sub>2</sub>O or HCHO) Monitor



**Measures Formaldehyde concentration, Air Temperature and Humidity with user-settable alarm. Perfect for monitoring indoor air quality of areas affected by formaldehyde gas. Back stand for desktop display or can be wall mounted.**

### Applications:

Formaldehyde is used in the manufacture of many industrial and consumer goods. Emissions from some of these items can rise when moisture and heat increase. These emissions are a contributing factor to Sick Building Syndrome, which may lead to itchy eyes and throat, as well as headaches and dizziness.

- Glue
- Paint
- Insulation/Plywood/Fiberboard
- Timber Paneling/Particleboard
- Cosmetics
- Shampoos
- Soap Bars/Body Wash
- Lotions
- Toothpaste

### Features

- Alternately displays Formaldehyde concentration, Air Temperature, and Relative Humidity readings (cycles approximately every 6 seconds)
- Visible bright tri-colored LED indicator: Green <0.08ppm, Yellow = 0.08 to 0.79ppm, and Red = 0.80ppm and above
- LCD displays alarm icon, LED light turns red, and loud audible beeper sounds when indoor CH<sub>2</sub>O level exceeds set point (defaults at 0.08ppm); beeper can be temporarily turned off for false alarm
- Selectable CH<sub>2</sub>O unit as ppm or mg/m<sup>3</sup>
- "ZERO" Re-Calibration function
- Manual Temperature and Relative Humidity Compensation (adjustable)
- Designed with Electrochemical CH<sub>2</sub>O sensor
- CH<sub>2</sub>O Calibration function in fresh air
- Four display error codes for troubleshooting
- Low battery indicator
- Recover to factory setting function
- Complete with built-in stand, side cover, Universal AC Adaptor (multi-plugs US, EU, UK, and AU), and 4 AAA batteries

<span style="color: green;">●</span>	< 0.08ppm	Normal
<span style="color: yellow;">●</span>	= 0.08 to 0.79ppm	Caution
<span style="color: red;">●</span>	= 0.80ppm & above	Danger

Bright Tri-colored LED Indicator for CH<sub>2</sub>O Level

Specifications	Range	Resolution	Basic Accuracy
Formaldehyde (CH <sub>2</sub> O or HCHO)	0.00 to 5.00ppm (mg/m <sup>3</sup> )	0.01ppm (mg/m <sup>3</sup> )	±5% of reading + 0.03ppm
Air Temperature	32 to 122°F (0 to 50°C)	0.1°F/1°C	±2°F/1°C
Humidity	20 to 90%RH	1%RH	±5%RH
Dimensions	4.4x4.3x2.1" (113x108x53mm)		
Weight	5.6oz (159g)		

### Ordering

FM100..... Formaldehyde Monitor



UPC Code: 793950231005

