



ExStik® Waterproof Refillable pH Meter

Features flat surface electrode, RENEW and

CALibration alerts, memory, and bargraph

Indicator tells you it's time to replace your electrode and eliminates guesswork

Features:

- ✓ Refillable pH electrode is easily serviced. Fresh reference solution maintains high accuracy. Eliminates concern with shelf life.
- ✓ Flat Surface Electrode measures pH in liquids, semi-solids, and solids. No more electrode breakage or clogged junctions.
- ✓ CAL alerts tells you it's time to recalibrate. Ensures accuracy.
- ✓ Memory records and recalls 15 sequentially tagged readings. Allows detection of changes over time.
- · Analog bargraph displayed on LCD.

Shows trends in acidity or alkalinity.

- · 1, 2 or 3 point calibration automatically recognizes buffer solutions. Order pH buffers separately.
- · Automatic Temperature Compensation
- · Simultaneous display of pH and Temperature
- · Waterproof to IP57 standard
- · Display indicates when the reading is stabilized
- · Data Hold, Auto power off and low battery indication
- · Waterproof design floats in water and

protects the meter in wet environment

- · Interchangeable probes available for Chlorine & ORP
- · Optional weighted base (EX006) holds plastic cup and ExStikภ meter
- · Complete with refillable flat surface pH electrode, 1.5mL bottle

KCI, 2 reference junctions, 2 removal tools, protective sensor cap, sample cup with cap, four 3V CR-2032 button batteries, and 48" (1.2m) neckstrap. Order pH buffers separately

Ordering Information:

PH110	Waterproof Refillable ExStikฏ pH Meter
PH115	Spare Refillable pH ExStikฏ Electrode Module
PH113	Reference Refill Solution Kit for PH110
EX006	Weighted base with 5 solution cups
PH103	Tripak buffers (6ea - 4, 7, 10pH & 2 Rinse solutions)
PH105	Spare pH ExStikg Electrode Module
EX007	Spare sample solution cups (24pk)
CA903	Carrying case for ExStik™ kit
RE305	Spare Probe, ORP
CL205	Spare Probe, Chlorine
EX010	Extension Cable, 3ft (1 Meter) with probe weight for
EX050 .	Extension Cable, 16ft (5 Meter) with probe weight for

or ExStik or ExStik PH115Spare Probe, pH, Refillable Reference

PH4-P.....pH 4 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each PH7-P.....pH 7 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each PH10-P.....pH 10 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each

CA895Carrying Case, Small with Belt Loop Ex800.....ExStik 3-in-1 Kit (Chlorine, pH, Temp) **EX900**.....ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)

DO610ExStik DO/pH/Conductivity Kit







1.5mL bottle KCI, 2 reference juctions and 2 removal tools.

Specifications	
pH	0.00 to 14.00pH
Temperature	23 to 194ฐF (-5 to 90ฐC)
Resolution	0.01pH, 0.1ฐ
Accuracy	0.01pH, ท1.8ฐF/ท1ฐC
Power	four LR44 button batteries
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm
Weight	3.8oz (110g)





18.6