

## ExStik® ORP Waterproof Meter



**Flat surface electrodes provides "On-the-Spot" measurements**

With  $\pm 4\text{mV}$  accuracy and high  $1\text{mV}$  resolution

### Features:

- Measures ORP from -999 to 999mV
- Automatic electronic self calibration
- Simulated analog bar graph displays change in ORP reading
- Memory stores and recalls 15 readings and saves last calibrated value
- Data validation indicators show user the reading is stabilized
- Large 3-1/2 digit (2000 count) Digital display with bar graph
- Data Hold, Auto shut-off and low battery indication
- Easy to replace electrode module is interchangeable with pH and chlorine ExStik modules; (built in chip automatically recognizes the type of probe plugged in for specific measurements)
- Waterproof (IP57) design floats in water and protects the meter in wet environment
- Complete with meter and electrode, protective sensor cap, sample cup, four 3V CR-2032 batteries, and neckstrap
- Optional weighted base (EX006) holds plastic cup and ExStik meter



Flat surface Electrodes work in liquids, semi-solids and solids



Optional Weighted base (Model EX006)

### Ordering Information:

- RE300.....ExStik® ORP Meter  
 EX006 .....Weighted base with 5 solution cups  
 EX007 .....Spare sample solution cups (24pk)  
 CA903.....Carrying case for ExStik™ kit  
 RE305.....Spare Probe, ORP  
 PH105.....Spare pH ExStik® Electrode Module  
 PH115.....Spare Probe, pH, Refillable Reference  
 CL205 .....Spare Probe, Chlorine  
 EX010 .....Extension Cable, 3ft (1 Meter) with probe weight for ExStik  
 EX050 .....Extension Cable, 16ft (5 Meters) with probe weight for ExStik  
 CA895.....Carrying Case, Small with Belt Loop  
 EX800 .....ExStik 3-in-1 Kit (Chlorine, pH, Temp)  
 EX900 .....ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)

Specifications	
ORP (mV)	999 to 999mV
Resolution	1mV
Accuracy	4mV
Power	four SR44W button batteries
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)
Weight	3.85oz (110g)

สนใจติดต่อ บริษัท เอเมท จำกัด โกสุมรว่มใจ 31 ซอย 37 แยก 2 ดอนเมือง กทม 10210

โทร.02-5038900 , 02-5038929 , แฟกซ์ : 02-9810181 , Email : [sales@amet.net](mailto:sales@amet.net) , Web: [www.amet.net](http://www.amet.net)

สนใจติดต่อ บริษัท เอเม็ท จำกัด 4/2, 4/60, 4/61 ถ.สุคนธสวัสดิ์ 30 แขวงลาดพร้าว เขตลาดพร้าว กทม. 10230

โทร.02-9079421 , 02-9079878, แฟกซ์ : 02-9079878 , Email : [sales@amet.net](mailto:sales@amet.net) , Web: [www.amet.net](http://www.amet.net)

