

Precision Hygro-Thermometer



Highest 2% RH accuracy

With Grains per Pound (GPP) and Grams per Kilogram (g/kg) measurement

Features:

- Less than 30 second RH response time
- Water vapor in GPP (g/kg)
- Dual backlit display
- Simultaneous display of:
Humidity or GPP (g/kg) plus Temperature
Humidity or GPP (g/kg) plus Dew Point
Humidity or GPP (g/kg) plus Wet Bulb
- Slim design with rubberized sides for better grip and for one hand operation
- Data Hold and Min/Max functions
- Auto power off with disable and low battery indicator
- Complete with carrying case and 9V battery



Specifically designed for HVAC and
water damage restoration contractors



| Specifications | |
|------------------------|-----------------------------|
| Humidity | 0 to 100%RH |
| Temperature (Internal) | -22 to 199°F (-30 to 100°C) |
| Basic Accuracy | ±2%RH, ±1.8°F/1°C |
| Max. Resolution | 0.1%RH, 0.1°F/°C |
| Dewpoint | -22 to 199°F (-30 to 100°C) |
| Wet Bulb | 32 to 176 °F (0 to 80°C) |
| Absolute Humidity | 0 to 1120GPP (0 to 160g/kg) |
| Dimensions | 7.8x1.7x1.3" (200x45x33mm) |
| Weight | 7oz (200g) |

Ordering Information:

RH490Precision Hygro-Thermometer

RH490-NISTPrecision Hygro-Thermometer w/NIST

สนใจติดต่อ บริษัท เอเมท จำกัด โกสุมร่วมใจ 31 ซอย 37 แยก 2 ดอนเมือง กทม 10210

โทร.02-5038900 , 02-5038929 , แฟกซ์ : 02-9810181 , Email : sales@amet.net , Web: www.amet.net