

Hygro-Thermometer + InfraRed Thermometer



Humidity and Air Temperature measurements

Plus InfraRed Thermometer for non-contact surface Temperature

Features:

- Combination Humidity meter plus InfraRed Thermometer features a super large backlit dual display
- Primary and Secondary displays – Primary display is user selectable for IR or Humidity; Secondary always displays ambient temperature
- InfraRed thermometer has built in laser pointer and has an 8:1 distance to target ratio
- MAX and Data Hold for all functions
- Remote humidity sensor with 39" (1m) coiled cable provides readings for both humidity and ambient temperature
- Switchable $^{\circ}\text{C}/^{\circ}\text{F}$ temperature units
- Auto Power off to save battery life
- Low battery and overrange indication
- Complete with built-in stand, protective holster, Humidity/Temperature probe, 9V battery, and carrying case

Applications:

- Monitor Relative Humidity and Temperature in factories, clean rooms, offices, and greenhouses
- Non-contact InfraRed surface temperature measurements in hard to reach areas such as heating and air conditioning ducts



Specifications	Range	Max Resolution	Basic Accuracy
Humidity	10% to 95%	0.1%	3.5%
InfraRed Temperature	-58 to 932F (-50 to 500C)	0.1	2% or 4F/2C
Air Temperature	-4 to 140F (-20 to 60C)	0.1	3F/C
Emissivity	0.95		
Field of View	8:1		
Dimensions	5.9 x 2.95 x 1.57" (150 x 75 x 40mm)		
Weight	7oz (200g)		

Ordering Information:

RH101Hygro-Thermometer + InfraRed Thermometer

สนใจติดต่อ บริษัท เอเมท จำกัด โกสุมร่วมใจ 31 ซอย 37 แยก 2 คอนเมือง กทม 10210

โทร.02-5038900 , 02-5038929, แฟกซ์ : 02-9810181 , Email : sales@amet.net , Web: www.amet.net